










M12 线对线 螺纹组装系列

M12 line to line thread assembly series

描述 Description	组装式, 螺纹, 焊接 Assembled, threaded, welded		组装式, 螺纹, 焊接 Assembled, threaded, welded	
照片 Photographs				
尺寸 Dimensions	 公 Male		 母 Female	
料号 Part Number	芯数 Contacts	料号 Part Number	芯数 Contacts	料号 Part Number
	2	XQ-B0-010201-04-XXXX CQC	2	XQ-B0-020201-04-XXXX CQC
	3	XQ-B0-010301-04-XXXX CQC	3	XQ-B0-020301-04-XXXX CQC
	4	XQ-B0-010401-04-XXXX CQC	4	XQ-B0-020401-04-XXXX CQC
芯数 Core Number	 2 Pin	 3 Pin	 4 Pin	
额定电流/电压 Current/voltage rated	10A/300V	10A/300V	10A/300V	
接触件直径 Contact diameter	Φ1.5			
防水等级 Water proof grade	IP68			
线材规格 Cable Gauge	0.3mm <sup>2</sup> -1.0mm <sup>2</sup> (22-16AWG)			
线材外径 Cable OD	≤8mm			
工作温度 Operating temperature	尼龙 -40℃--+105℃			






M12 面板式 螺纹组装系列

M12 panel type thread assembly series

描述 Description	后装公面板, 螺纹, 焊接 Rear mounted male panel, threaded, welded		前装公面板, 螺纹, 焊接 Front male panel, threaded, welded	
照片 Photographs				
尺寸 Dimensions				
料号 Part Number	芯数 Contacts	料号 Part Number	芯数 Contacts	料号 Part Number
	2	XQ-B0-050201-03-XXXX CQC	2	XQ-B0-060201-03-XXXX CQC
	3	XQ-B0-050301-03-XXXX CQC	3	XQ-B0-060301-03-XXXX CQC
	4	XQ-B0-050401-03-XXXX CQC	4	XQ-B0-060401-03-XXXX CQC
芯数 Core Number	 2 Pin		 3 Pin	
额定电流/电压 Current/voltage rated	10A/300V		10A/300V	
接触件直径 Contact diameter	φ1.5			
防水等级 Water proof grade	IP68			
线材规格 Cable Gauge	0.3mm <sup>2</sup> -1.0mm <sup>2</sup> (22-16AWG)			
线材外径 Cable OD	≤8mm			
工作温度 Operating temperature	尼龙 -40℃-+105℃			

M12 螺纹 尼龙/PVC 注塑系列

M12 thread nylon/PVC injection molding series

描述 Description	组装式, 螺纹, 焊接 Assembled, threaded, welded			组装式, 螺纹, 焊接 Assembled, threaded, welded		
照片 Photographs						
尺寸 Dimensions						
料号 Part Number	芯数 Contacts	料号 Part Number		芯数 Contacts	料号 Part Number	
	2	XQ-B0-010201-05-XXXX CQC		2	XQ-B0-020201-05-XXXX CQC	
	3	XQ-B0-010301-05-XXXX CQC		3	XQ-B0-020301-05-XXXX CQC	
	4	XQ-B0-010401-05-XXXX CQC		4	XQ-B0-020401-05-XXXX CQC	
芯数 Core Number	 2 Pin		 3 Pin		 4 Pin	
额定电流/电压 Current/voltage rated	10A/300V		10A/300V		10A/300V	
接触件直径 Contact diameter	φ1.5					
防水等级 Water proof grade	IP68					
线材规格 Cable Gauge	0.3mm <sup>2</sup> -1.0mm <sup>2</sup> (22-16AWG)					
线材外径 Cable OD	≤8mm					
工作温度 Operating temperature	尼龙 -40℃-+105℃ / PVC-40℃-+80℃					